



DATA SHEET DIGITAL PRINTING ANTI GRAFFITI PERMANENT ADHESIVE

**AG700**

36 micron polyester film coated with a pressure sensitive acrylic adhesive. Gloss surface finish for cold lamination.

**SPECIFICATIONS:**

|  | <u>Average values</u> | <u>Standard</u> |
|--|-----------------------|-----------------|
| • Thickness (µm):  | 36                    |                 |
| • Tensile strength (N/25mm):                             | > 100                 | HEXNFX4102I     |
| • Elongation at break (%):                               | N/A                   | HEXNFX4102I     |
| • Dimensional stability (mm):<br>after 168 hours at 70°C | < 0.2                 | HEXRET00I       |
| • Surface roughness (µm):                                | < 5*                  | HEXRUG00I       |

\* A surface roughness of less than 10 microns is potentially dangerous in flooring under damp conditions. Do not use on flooring.

**LINER:**

- Silicon liner paper 80 g/m<sup>2</sup> grey HEXIS print.
- Stable under hygrometric variations.

**ADHESIVE PROPERTIES:**

- |  |      |           |
|--|------|-----------|
| • Adhesion on glass, 180° peel (N/25mm):<br>20 minutes after application                                     | 11   | HEXFTM00I |
| 24 hours after application   | 13   |           |
| • Initial tack (N/25mm):   | 8    | HEXFTM009 |
| • Release (N/25mm):  | 0,20 | HEXFTM003 |
| • Resistance to solvents : the adhesive is resistant to most chemical agents (alcohol, diluted acids, oils). |      |           |

**RECOMMENDATIONS:**

- Minimum application temperature +10°C (+50°F).
- Optimum environment -40°C to +90°C (-40°F to +194°F).
- Acrylic solvent based adhesive (not removable adhesive).
- Immediate and permanent adhesion, suitable for wet application.
- The film may be cleaned with acetone, alcohol or soapy water.
- Do not use abrasive sponges.

**SHELF LIFE:**

- 2 years at +15°C...+25°C (+50°F...+77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

**DURABILITY:**

- Vertical exposure: depending on cleaning.

**Note:**

If in doubt about the compatibility of the product with any particular application we recommend that the user carry out a trial before the final application or seek advice from the manufacturer. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force. All data are believed to be correct but do not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The buyer has to determine the suitability of the materials for the intended purpose prior to purchase. HEXIS S.A. or its affiliates assume no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: [www.hexisgroup.com](http://www.hexisgroup.com).