



DATA SHEET DIGITAL PRINTING ANTI GRAFFITI PERMANENT ADHESIVE

AG700

36 micron polyester film coated with a pressure sensitive acrylic adhesive. Gloss surface finish for cold lamination.

SPECIFICATIONS:

	<u>Average values</u>	<u>Standard</u>
• Thickness (µm):	36	
• Tensile strength (N/25mm):	> 100	HEXNFX4102I
• Elongation at break (%):	N/A	HEXNFX4102I
• Dimensional stability (mm): after 168 hours at 70°C	< 0.2	HEXRET00I
• Surface roughness (µm):	< 5*	HEXRUG00I

* A surface roughness of less than 10 microns is potentially dangerous in flooring under damp conditions. Do not use on flooring.

LINER:

- Silicon liner paper 80g/m² grey HEXIS print.
- Stable under hygrometric variations.

ADHESIVE PROPERTIES:

- | | | |
|---|------|-----------|
| • Adhesion on glass, 180° peel (N/25mm):
20 minutes after application | 11 | HEXFTM00I |
| 24 hours after application | 13 | |
| • Initial tack (N/25mm): | 8 | HEXFTM009 |
| • Release (N/25mm): | 0.20 | HEXFTM003 |
| • Resistance to solvents: the adhesive is resistant to most chemical agents (alcohol, diluted acids, oils). | | |

RECOMMENDATIONS:

- Minimum application temperature +10°C (+50°F).
- Optimum environment -40°C to +90°C (-40°F to +194°F).
- Acrylic solvent based adhesive (not removable adhesive).
- Immediate and permanent adhesion, suitable for wet application.
- The film may be cleaned with acetone, alcohol or soapy water.
- Do not use abrasive sponges.
- In the case of painted substrates self-adhesive media must only be applied onto the undamaged original paintwork. If the paint is not the original paintwork and/or if it is damaged, the application and the removal are at the installer's risk.

SHELF LIFE:

- 2 years at +15 °C to +25 °C (+50 °F to +77 °F) and 50 % relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

DURABILITY:

- Outdoor vertical exposure, film without graffiti, before any cleaning with solvents: 3 years
- Cleaned film: depending on cleaning method and frequency

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application.

The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.