



DATA SHEET DIGITAL PRINTING BANNER FRONT2

High tolerance polyester banner coated with plastic 400 micron PVC, for solvent inkjet printing. Satin surface finish. Inkjet varnish on one side.

SPECIFICATIONS:

| | <u>Average values</u> |
|--|-----------------------|
| • Total caliper (µm): | 400 |
| • Total specific weight (g/m ²): | 575 |
| • Opacity (%): | 94 |

PRINTER AND INK COMPATIBILITY:

- Solvent printers.

RECOMMENDATIONS:

- Touch dry after less than 5 minutes depending on printer used.
- For all covering, optimum drying time for inks is 24 hours.
- Optimum environment +10°C to +30°C (+50°F to +86°F) at 30 to 70% humidity.
- Optimum storage temperature of the banner: -30 to +70°C (-22°F to +158°F)
- High frequency (H.F.) sealing may be used.
- May be made up using Neoprene[®] glue (I). or double-sided self-adhesive tape of the type STRONBAN.

SHELF LIFE:

- 1 year at +15°C...+25°C (+59°F...+77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

DURABILITY:

- Vertical outdoor exposure: 3 years.

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force. All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.