



DATA SHEET DIGITAL PRINTING BANNER FRONT3

450 g/m² plasticized PVC coated Polyester banner, for solvent inkjet printing. Matt surface finish.

SPECIFICATIONS:

Average values

- Total specific weight (g/m²): 450

PRINTER AND INK COMPATIBILITY:

- Solvent printers.

RECOMMENDATIONS:

- Touch dry after less than 5 minutes depending on printer used.
- For all covering, optimum drying time for inks is 24 hours.
- Optimum environment +10°C to +30°C (+50°F to +86°F) at 30 to 70% humidity.
- Optimum storage temperature of the banner: -30 to +70°C (-22°F to +158°F)
- High frequency (H.F.) sealing may be used.
- May be made up using Neoprene[®] glue (1).

SHELF LIFE:

- 1 year at +15°C...+25°C (+59°F...+77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

DURABILITY:

- Vertical outdoor exposure: 1 year.

Note:

If in doubt about the compatibility of the product with any particular application we recommend that the user carry out a trial before the final application or seek advice from the manufacturer. All data are believed to be correct but do not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The buyer has to determine the suitability of the materials for the intended purpose prior to purchase. HEXIS S.A. or its affiliates assume no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.

(1) Neoprene[®] is a registered Trademark of E.I. Du Pont de Nemours and Company.