



DATA SHEET DIGITAL PRINTING BANNER FRONT3v2

450 g/m² plasticized PVC coated Polyester banner, for solvent and eco-solvent inkjet printing. Printable on smooth face. Matt surface finish.

SPECIFICATIONS:

	<u>Average values</u>
• Total caliper (µm):	400
• Total specific weight (g/m ²):	450

PRINTER AND INK COMPATIBILITY:

- Solvent or eco-solvent printers.

RECOMMENDATIONS:

- Touch dry after less than 5 minutes depending on printer used.
- For all covering, optimum drying time for inks is 24 hours.
- Optimum environment +10°C to +30°C (+50°F to +86°F) at 30 to 70% humidity.
- Optimum storage temperature of the banner: -30 to +70°C (-22°F to +158°F)
- High frequency (H.F.) sealing may be used.
- May be made up using Neoprene® glue (I) or double-sided self-adhesive tape of the type STRONBAN.

SHELF LIFE:

- 1 year at +15°C to +25°C (+59°F to +77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.