



DATA SHEET DIGITAL PRINTING BANNER FRONT4

Banner made of a polyester weave laminated with plasticised PVC both sides, 470 g/m², for solvent inkjet printing. Printable on smooth face. Matt surface finish.

SPECIFICATIONS:

Average values

- Total specific weight (g/m²): 470

PRINTER AND INK COMPATIBILITY:

- Solvent printers.

RECOMMENDATIONS:

- Printable on smooth face.
- Touch dry after less than 10 minutes depending on printer used.
- Before varnishing or installation, optimum drying time for inks is 24 hours.
- Optimum environment +10°C to +30°C (+50°F to +86°F) at 30 to 70% humidity.
- Optimum storage temperature of the banner: -30 to +70°C (-22°F to +158°F)
- High frequency (H.F.) and hot-air sealing may be used.
- Ideal for short term outdoor signage and banners.

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force. All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.