



POLYESTER TAPE DATA SHEET DIGITAL PRINTING

HEX 600

Transparent 100 micron polyester film, coated with a pressure sensitive acrylic adhesive.

SPECIFICATIONS:

Average values

- Total caliper (µm): 100

ADHESIVE PROPERTIES:

- Peel on steel (N/cm): low to average

RECOMMENDATIONS:

- Tape recommended for use with FLEXPRINT3.

ADHESIVE:

- Acrylic.

SHELF LIFE:

- 1 year at +15°C...+25°C (+59°F...+77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

Note:

If in doubt about the compatibility of the product with any particular application we recommend that the user carry out a trial before the final application or seek advice from the manufacturer. All data are believed to be correct but do not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The buyer has to determine the suitability of the materials for the intended purpose prior to purchase. HEXIS S.A. or its affiliates assume no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.