



## PRODUCT DATA SHEET

### VR 7077

Edge sealing varnish for use around edge of digital prints in order to extend durability.

#### **COMPOSITION:**

- Xylene
- Acrylic polymer

#### **CHARACTERISTICS:**

- Colourless to light yellow liquid

#### **USER'S GUIDE:**

- Apply print onto target surface.
- In order to properly apply the varnish, use a masking tape 5mm away from the edge around the print. Do the same on the print at 5mm from the edge. Be careful to ensure that the edges of the print adhere well.
- Apply only to dry surfaces (print and substrate).
- Apply varnish with supplied brush in one coat.
- Remove masking tape within 15 minutes of application.
- The drying time depends on the thickness of the coat and the temperature. For a film with ink overload the optimum drying time is 24 hours. Any mechanical interference (cleaning, abrasion ...) must absolutely be avoided during that time.
- Do not smoke during application.
- Handle only in ventilated areas.
- Use gloves and protective goggles.
- Refer to Health and Safety Data Sheet.
- Once applied, the VR 7077 may be dissolved with acetone.

#### **STORAGE:**

- Keep container tightly closed in a cool and ventilated place; store away from flames or sparks. Do not smoke.
- Shelf life: 1 year if stored unopened in the original container.

#### **Note:**

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: [www.hexisgroup.com](http://www.hexisgroup.com).