



## PROTECTIVE FILM - DATA SHEET

### AUTO 35 TI

**Thermoformable** solar protection film for motor vehicles. Interior application.

Colour: Light Titanium.

#### **SPECIFICATIONS:**

	<u>Average values</u>
• Thickness excluding liner (µm):	46
• Solar energy deflected (%):	57
• Light transmission (%):	35
• Visible light reflection (%):	10
• Maximum UV Transmission (%):	1

#### **FILM COMPATIBILITY:**

Standard clear glazing	Yes
Standard tinted glazing	Yes
Clear double glazing	No
Tinted double glazing	No

#### **PACKAGING:**

- Hanging reel:

	Width	Length
	1.523m	30.5m
	1.523m	15m
	500mm	6m
	760mm	2m

## **RECOMMENDATIONS:**

- Always handle with clean, dry hands when storing.
- Remove the liner at the last moment before application and mount the film immediately as instructed during the HEXIS training course.
- The film adheres virtually immediately, do not manipulate once applied.
- Adheres to smooth, non-grainy glass.
- Anti UV protection incorporated in the polyester. Minimal protection against discoloration of fabrics, leather and fittings.
- Scratch resistant coating: lengthens useful life and makes cleaning easy.
- Anti scratch test carried out on every production batch.
- Interior application.
- One direction thermoformable film.
- **Installation authorised on front windows but prohibited on the windscreen.**
- Specific tooling only for installing on motor vehicles.

## **SHELF LIFE:**

- Shelf life (before application):  
     1 year when stored horizontally in a dustfree place at between +15°C.... +25°C (+59°F.... +77°F) at 50% relative humidity.

## **DURABILITY:**

- Vertical exposure:  
     5 years (when installed by a HEXIS approved installer).

### **Note:**

The wide range of glazing available and constant innovations being made are bound to lead the user to consider further application possibilities for the product. When in doubt, request an expert evaluation of film and glass compatibility.

The information published is based on regular laboratory controls. However, it does not constitute a binding guarantee. The vendor declines liability for indirect damage, taking responsibility only for the competitive price of these products. Product specifications may change without prior notice. Our website is automatically updated: [www.hexisgroup.com](http://www.hexisgroup.com).