



PROTECTIVE FILM - DATA SHEET

BSE50I

50 microns safety film. Indoor application.
Colour: Transparent.

SPECIFICATIONS:

	<u>Average values</u>
• Thickness excluding liner (µm):	50
• Solar energy deflection (%):	19
• Light transmission (%):	88
• Visible light reflection (%):	8
• Absorption rate (%):	17
• Maximum UV Transmission (%):	1

FILM COMPATIBILITY:

Standard clear glazing	Yes
Standard tinted glazing	Yes
Clear double glazing	Yes
Tinted double glazing	Yes

PACKAGING:

- Hanging reel - width 1.523 metres, length 30.5 metres.

RECOMMENDATIONS:

- When stocking, always handle with clean, dry hands.
- Remove the liner at the last moment before application and mount the film immediately as instructed during the HEXIS training course.
- Adhesion is immediate. Do not peel the film once it has been applied.
- Adheres to smooth, non-grainy glass.
- Anti-UV protection in the adhesive.
- Anti-scratch coating for long durability and easy cleaning.
- The anti-scratch test is carried out during production.
- Indoor application.
- Use specific tools for building applications.

SHELF LIFE:

- Shelf life (before application) :
1 year when stored horizontally in a dustfree place at between +15°C.... +25°C (+59°F.... +77°F) at 50% relative humidity.

DURABILITY:

- Vertical exposure:
10 years (when installed by a HEXIS approved installer).

Note:

The wide range of glazing available and regular innovation oblige the user to consider the suitability of the product for each application. When in doubt, request an expert evaluation of the compatibility of film and glass.

The information published is based on regular laboratory controls. However, it does not constitute a binding guarantee. The vendor declines liability for indirect damage, taking responsibility only for the competitive price of these products. Product specifications may change without prior notice.

Our website is automatically updated: www.hexisgroup.com.