

RECOMMENDATIONS:

- Always handle with clean, dry hands when storing.
- Remove the liner at the last moment before application and mount the film immediately as instructed during the HEXIS training course.
- The film adheres virtually immediately, do not manipulate once applied.
- Adheres to smooth, non-grainy glass.
- Anti UV protection incorporated in the polyester. Minimal protection against discoloration of fabrics, leather and fittings.
- Scratch resistant coating: lengthens useful life and makes cleaning easy.
- Anti scratch test carried out on every production batch.
- Interior application.
- One direction thermoformable film.
- **Installation prohibited on front windows and on the windscreen.**
- Specific tooling only for installing on motor vehicles.

SHELF LIFE:

- Shelf life (before application):
1 year when stored horizontally in a dustfree place at between +15°C.... +25°C (+59°F.... +77°F) at 50% relative humidity.

DURABILITY:

- Vertical exposure:
3 years (when installed by a HEXIS approved installer).

Note:

The wide range of glazing available and constant innovations being made are bound to lead the user to consider further application possibilities for the product. When in doubt, request an expert evaluation of film and glass compatibility.

The information published is based on regular laboratory controls. However, it does not constitute a binding guarantee. The vendor declines liability for indirect damage, taking responsibility only for the competitive price of these products. Product specifications may change without prior notice.

Our website is automatically updated: www.hexisgroup.com.